

TDS TECHNICAL DATA SHEET

TECHNICAL DATA SHEET MAP C030/060/090/120/160cm x 270m Masking paper brown 50gr

Description

- Masking paper brown.
- 50 gr/m² recycled brown paper.
- No dust
- Available in 5 dimensions.

Technical info

Conditions : 23°C – 50% relative humidity

Properties	Standard	Unit		Tolerance
Substance	ISO 536	gr/m²	50	+/- 2
Absolute moisture	ISO 287	%	6	+/- 1
Cobb Test (60s)	ISO 535	gr/m²	25	+/- 5
Bursting strength	ISO 2758	Кра	120	+/- 30%
Tensile strength MD	ISO 1924 - 1/2	Nm/gr	50	+/- 10
Tensile strength CD	ISO 1924 - 1/2	Nm/gr	20	+/- 10
Wet tensile strength	ISO 3781	%	25	+/- 5

Storage and shelf life

Store in a dry and a well ventilated area.

The above information is given in good faith, but the user should assure himself that the performance of the product is sufficient for his application. The quoted values are average and should not be taken as maximum or minimum values for specific purposes. Chemicar Europe cannot be held responsible for product failure unless full testing has been carried out.

Chemicar Europe nv Baarbeek 2 2070 Zwijndrecht België-Belgium T.: +32 3 234 87 80 F.: +32 3 234 87 89 info@chemicar.eu www.chemicar.eu