FINIXA
paint processing products

TDS

TECHNICAL DATA SHEET

PPAS 0X



VARIETIES

PPAS 01	PAINT PREPARATION ABRASIVE SYSTEM	PRIMER PREP
PPAS 02	PAINT PREPARATION ABRASIVE SYSTEM	WET IN WET PRIMER PREP
PPAS 03	PAINT PREPARATION ABRASIVE SYSTEM	BASE COAT PREP
PPAS 04	PAINT PREPARATION ABRASIVE SYSTEM	BASE COAT / CLEAR COAT PREP

Intuitive, effective and high quality foam sanding disc with 75 holes. The ultimate solution for professional refinishing tasks that require seamless surface preparation. The unique grain structure allows the disc to perform multiple steps in one go and maximizes dust extraction.

COLOR	GREY
BASE	FILM
MATERIAL BACKING	FLEXIBLE FOAM
BONDING	RESIN OVER RESIN
COATING	OPEN COAT
STEARATE	ANTI-CLOGGING LAYER
GRIT	CUSTOMIZED MULTI-GRIT
PRODUCTION WIDTH	150MM -75 HOLES

RANGE OF GRITS

- PRIMER PREP - SANDING SPEED OF P180 / FINISH OF P240
- WET IN WET PRIMER PREP - SANDING SPEED OF P240 / FINISH OF P320
- BASE COAT PREP - SANDING SPEED OF P320 / FINISH OF P500-P600
- BASE COAT / CLEAR COAT PREP - SANDING SPEED OF P600 / FINISH OF P1000

WEIGHT	250 GR / BOX
PACKAGING	20 PCS PER BOX
OUTER PACKAGING	8 BOXES PER CARTON

SECTORS APPLICATIONS

These data are informative and non-binding. Chemicar Europe cannot be held responsible for any use made of this information. These are not specifications but typical characteristics.
The safety data sheet is available on request. Product characteristics may change when used with other products. All information is subject to change without notice.

Chemicar Europe nv
Baarbeek 2
2070 Zwijndrecht
België-Belgium

T.: +32 3 234 87 80
F.: +32 3 234 87 89
info@chemicar.eu
www.chemicar.eu