TECHNICAL DATASHEET

Date of creation	20-11-2026	**Number of pages**	1 / 4

Article number:	FOL 501MT
Description:	**FOL 501MT - Lifting tape 'multi' 9, 12, 20mm x 10m 1p.**
EAN:	5491196900680



The Finixa FOL 501MT Lifting Tape ‘Multi’ is a professional masking tape designed for automotive refinishing applications. Featuring two integrated plastic strips of different widths, this innovative tape allows technicians to temporarily lift rubber seals and trims away from vehicle panels, ensuring complete paint coverage and helping to prevent hard paint edges around windows, doors and body openings.

Finixa Multi Lifting Tape for Lifting Rubber Seals and Preventing Hard Paint Edges

Developed specifically for the automotive refinish industry, the Finixa FOL 501MT combines a high-temperature crepe masking tape with two plastic lifting strips in a single product. The dual-strip design allows for three masking configurations: using either strip individually or folding both strips together for larger gaps between rubber seals and body panels. This versatility reduces the need for multiple masking products and helps speed up preparation times.

The tape and plastic strips are perforated at regular intervals, allowing them to be torn by hand for quick application. Designed to withstand paint booth curing cycles up to 120°C, the tape remains reliable during automotive paint drying processes while protecting rubber trims from overspray and solvent exposure.

Key features

- Multifunctional lifting tape with two integrated plastic strips
- One product enables three different masking applications
- Designed to lift rubber seals away from vehicle panels for concealed paint coverage
- High-temperature masking tape resistant up to 120°C
- Hand-tearable perforations for quick and easy use
- Flexible construction follows contours and tight curves
- Helps prevent hard paint edges around trims and window rubbers

Date of creation	20-11-2026	**Number of pages**	2 / 4

Product details

- Brand: Finixa
- Number: FOL 501MT
- EAN: 5491196900680
- Colour: Beige
- Length: 10 m
- Width: 50 mm
- Shelf life: 12 months
- Dry storage: Yes
- Storing condition: Dark
- Freezing resistant: Yes
- Units for outer box: 10
- Units for pallet: 1080
- Elongation: 9 %
- Foldable use: No
- Maximum processing temperature: 120°C / max. 30 min
- Maximum temperature resistance: 120 °C
- Perforated: Yes
- Perforation spacing: 42 mm
- Tensile Strength: 34 kg/cm^2
- Thickness: 0.265 µm

Date of creation	20-11-2026	Number of pages	3 / 4

Application

Insert one plastic strip, both strips, or the folded combination of both strips between the rubber seal and the vehicle panel. Attach the adhesive tape to the glass surface and gently pull the rubber seal away from the panel. This creates a gap that allows paint to reach behind the rubber, producing a cleaner finish and eliminating hard paint edges after the masking materials are removed. The perforated design allows the tape to be torn easily by hand for fast application.

Frequently Asked Questions

- **What is lifting tape used for?**
  Lifting tape is designed to temporarily lift rubber seals and trims away from vehicle panels during painting, allowing paint coverage underneath and preventing hard paint edges.
- **Why does the tape include two plastic strips?**
  The two-strip design allows three different masking configurations, making one tape suitable for various vehicle sealing and trim profiles.

TECHNICAL DATASHEET

Date of creation	20-11-2026	Number of pages	4 / 4

Related Products



FOL 51ET

FOL 51ET - Lifting tape 'Easy Tear' 10mm x 10m 1p.



MST 919-950

MST - Masking tape 100° 50m

Disclaimer
It is the user's responsibility to read, understand, and apply the information contained in this technical data sheet. The products are for professional use only. The necessary protective equipmentand clothing must be worn. Repairs must always be carried out in accordance with the guidelines and regulations of the original equipment manufacturers. Allinformation must be considered, researched, and verified by the user. The specific use, application, and conditions of use are beyond the control of EMM InternationalBV. It is the user's responsibility to determine the suitability of the product for their specific application

Bohemenstraat 19, 8028SB Zwolle, The Netherlands +31(0)38 467 66 00 E

EMM International BV E sales@emm.com **www.finixa.com**